


# X Series

for interference Suppression  
and Across-The-Line, Class X2



## Feature

X series is self-healing flat style capacitor, which is wound with polypropylene film dielectric, flame retardant, plastic case and epoxy resin end seal. Following styles belong to this series:

S=Tinned copper clad steel wire radial leads.

P=UL 1015 or 1017 AWG#20~22 solid PVC insulation wire radial leads.

X series is especially designed for radio interference suppression and across-the-line capacitors in:

- (1) Business machine's appliance, such as typewriter, computer display and monitor.
- (2) Household appliance, such as mixer, fan, coffee grinder, audio and TV circuit.
- (3) Thyristor and triac appliance, such as dimmer, power supply.

## Specifications

Climate category	In accordance with DIN40040 GPF
Voltage Range	250V.(UL.CSA)/275V.AC,50~60Hz
Capacitance Range	0.0047-1.00uF
Capacitance Tolerance	J(±5%), K(±10%), M(±20%)
Withstand Voltage	1,200V.AC(60Hz)for 60 sec. or 2,100V.DC for 1 sec.
Dissipation Factor	≤ 0.1% at 1 K Hz and 20°C ≤ 0.3% at 10 K Hz and 20°C
Insulation Resistance (between terminals)	≥ 3x10 <sup>4</sup> MΩ for C≤0.33uF ≥ 1x10 <sup>4</sup> MΩ / uF for C>0.33uF

G(Minimum Limit Temperature)=-40°C

M(Maximum Limit Temperature)=+100°C

F(Humidity Category)=average relative humidity≤75%

95% for 30 days per year continuously

85% for the remaining days occasionally

J=±5%, K=±10%, M=±20%

Chip Type SMD

Miniature Type

General Purpose

High Frequency  
Low Impedance

High Voltage  
High Reliability

Non-polar Type

Large Size  
Snap-in

Large Size  
Screw





